

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A method of detecting an antigen proximally associated with a solid test surface, comprising:  
  
providing a roller surface, wherein the roller surface further comprises a binding agent that specifically binds at least part of the antigen;  
  
contacting at least part of the solid test surface with at least part of the roller surface such that the binding agent binds the antigen to form a bound antigen; and  
  
detecting the bound antigen on the roller surface.
2. (Original) The method of claim 1 wherein the step of contacting comprises repeatedly contacting the at least part of the test surface with the at least part of the roller surface.
3. (Original) The method of claim 1 wherein the test surface is selected from the group consisting of a skin, a meat for consumption, and a mucous membrane.
4. (Original) The method of claim 1 wherein the test surface is selected from the group consisting of a counter top, a door handle, a toilet seat, and a tile.
5. (Original) The method of claim 1 wherein the roller surface has a cylindrical configuration.
6. (Original) The method of claim 1 wherein the roller surface has a spherical configuration.
7. (Original) The method of claim 1 wherein the roller surface further comprises microspheres.
8. (Original) The method of claim 1 wherein the roller surface comprises cellulose.
9. (currently amended) The method of claim 7 [1] wherein the microspheres comprise cellulose.

10. (Original) The method of claim 1 wherein the binding agent comprises an antibody.
11. (Original) The method of claim 1 wherein the step of detecting the bound antigen further comprises a step of washing the bound antigen.
12. (currently amended) The method of claim 1 wherein the step of detecting the bound antigen comprises a ~~chromogenic~~ reaction in which a chromogenic substance is converted to a chromophore.
13. (currently amended) The method of claim 1 wherein the step of detecting the bound antigen comprises illumination of a fluorophor and detection of [a] light emitted from the fluorophor.
14. (currently amended) A method of detecting an antigen proximally associated with a solid test environment, comprising:  
  
providing a plurality of microbeads, wherein the plurality of microbeads is coupled to a detector surface, and wherein a binding agent that specifically binds at least part of the antigen is coupled to the plurality of microbeads;  
  
repeatedly contacting the solid test environment with the detector surface such that a complex between the binding agent and the antigen is formed; and  
  
detecting the complex on the detector surface.
15. (Original) The method of claim 14 wherein the detector surface has a configuration selected from the group consisting of a flat configuration, a cylindrical configuration, and a spherical configuration.
16. (Original) The method of claim 14 wherein the detector surface and the microbeads comprise cellulose.
17. (Original) The method of claim 14 wherein the solid test environment comprises a liquid.
18. (Original) The method of claim 14 wherein the binding agent comprises an antibody.

19. (Original) The method of claim 14 wherein the step of detecting further comprises washing the complex.
20. (Original) The method of claim 14 wherein the step of detecting further comprises incubation of the complex with a secondary antibody.
21. (currently amended) An apparatus for detecting an antigen proximally associated with a solid test surface, comprising:  
  
a housing with a handle;  
  
a contactor rotatably coupled to the housing, wherein the contactor comprises a roller surface sized and dimensioned to reciprocally contact at least part of the solid test surface; and  
  
wherein the roller surface further comprises a binding agent that specifically binds at least part of the antigen.
22. (Original) The apparatus of claim 14 wherein the binding agent comprises an antibody.
23. (Original) The apparatus of claim 14 further comprising at least one of a light source and a light detector.
24. (Original) The apparatus of claim 14 wherein the roller surface has one of a spherical configuration and a cylindrical configuration.